



# Petrol Gasoline Compactor

## KGC - GX 55 HP



|                |                         |
|----------------|-------------------------|
| Ram plate size | : 300x800 mm            |
| Impact depth   | : 10 cm                 |
| Tamping depth  | : 35 CM                 |
| Machine weight | : 82 KG                 |
| Power type     | : Honda GX 160 Gasoline |
| Power          | : 5.5 HP                |
| Impact         | : 60 N.m                |
| Impact times.  | : 450-700 Times/min     |
| Takeoff height | : 45-70 mm              |
| IForward speed | : 9-13 m/min            |

## Product Feature

- This equipment is ideal for creating roadbeds, bridges, reservoirs, dams, walls, and various ditches, as well as other narrow areas for roads and railways.
- It is capable of handling construction tasks that larger and medium-sized machinery may not be able to accomplish.
- The robust closed air filter system is simple to clean, and the engine is designed to resist damage.
- The adjustable stroke allows for compaction of various soils and asphalt surfaces.
- The shock-absorbing guide handle helps minimize operator fatigue.

## Honda Engine GX 160



- 4-stroke single cylinder, OHV petrol engine, 25° inclined cylinder, Horizontal shaft
- Cast iron sleeve
- Displacement 163 cm<sup>3</sup>
- Engine Torqu Power 10.3 Nm / 1.05 kgfm / 2500 rpm
- Fuel Cons. At Cont. Rated Power 1.4 L/h - 3600 rpm
- Fuel Tank Capacity 3.1 Liter